

STEP

structures de données

Alain Muller

Télécom SudParis

October 3, 2024

1 Imported domains

```
import entity from "ri.newgen"  
  
import expression from "ri.newgen"  
  
import effect from "effects.newgen"  
  
import statement from "ri.newgen"
```

2 STEP domains

2.1 The `step_directives` resource

The resource `MODULE.step_directives` is produced par the `step_parser` phase and used by the `step_analyse` and `step_compile` phases.

The `map_entity_int` domain is used in `step_bison_parser.c`.

```
map_entity_int = entity->int
```

Domains used in `step_bison_parser.c`, `parser.c`, `directives.c`, `compile.c`

```
step_clause = reduction:map_entity_int + private:entity*  
+ shared:entity* + transformation:int + nowait:unit +  
threadprivate:entity* + copyin:entity* + firstprivate:entity*  
+ schedule:string*
```

Domains used in `step_bison_parser.c`, `parser.c`, `directives.c`, `analyse.c`, `compile.c`

```

    step_directive = type : int x persistent block : statement x
    clauses : step_clause*

```

```

    step_directives = persistent statement->step_directive

```

2.2 The `step_comm` resource

The resource `PROGRAM.step_comm` is initialized by the `step_analyse_init` phase, updated by the `step_analyse` phase and used by the `step_compile` phase.

Domains used in `analyse.c`

```

map_effect_bool = persistent effect -> bool

```

The origins of a SEND (and RECV) region is tracked by the `step_point` and `map_effect_step_point` domains. For a SEND (or RECV) region, the `step_point` associated in the `map_effect_step_point` table gives the previous SEND (or RECV) region before propagation (fields `module`, `stmt` and `data`).

```

    step_point = module : entity x persistent stmt : statement x
    persistent data : effect

```

```

    map_effect_step_point = persistent effect -> step_point

```

Domains used in `analyse.c`, `compile.c`

```

    step_comm = path: map_effect_step_point x interlaced:
    map_effect_bool x partial: map_effect_bool

```